

....a door to be trusted.

| SINCOL 45 | 45mm thick FD30 exterior door blank with concealed lipping. FSC Certified. | | |
|-------------------------------------|--|---------------------------------------|-----------------------------|
| Norsound sea perimeter | l configuration | glazing | d B rating |
| NOR710 | NOR810 | n/a | 32dB |
| NOR710 | NOR810 | 6mm Pyroshield | 33dB |
| NOR710 | NOR810 | 10mm Pyrodur | 34dB |
| NOR710 | NOR810 | 11mm Pyroguard C | 34dB |
| | | | |
| SINCOL 54 | 54mm thick FD60 | O exterior door blank with hardwood o | core and concealed lipping. |
| | 54mm thick FD60 I configuration threshold | exterior door blank with hardwood o | dB rating |
| Norsound sea | l configuration | | |
| Norsound sea perimeter | l configuration threshold | glazing | dB rating |
| Norsound sea perimeter NOR710 | l configuration threshold NOR810 | glazing n/a | dB rating 35dB |



Suite 9, Brookside House Spring Road Ibstock LE67 6LR t. 01503 264 266 f. 01503 264 226 email: sincoluk@aol.com

NOR710



NOR810

By buying products with the FSC label you are supporting the growth of responsible forest management worldwide

SW-COC-002681

15mm Pyrostop

© 1996 Forest Stewardship Council A.C. SINCOL carries FSC certification, subject to availability



Norseal House Regents Drive Prudhoe NE42 6PX t. +44 (0)1661 83 00 88 f. +44 (0)1661 83 00 99

36dB

w. www.norsound.co.uk
e. sales@norsound.co.uk

SINCOL door blanks and **NORSOUND** acoustic seals. Making **sound** sense.



....a door to be trusted.

| door characteristics | SINCOL 45 | SINCOL 54 |
|--|-----------------|----------------|
| FSC certified | √ | √ |
| 30 minutes fire-rated (tested beyond 42mins) | | n/a |
| 60 minutes fire-rated (tested beyond 68mins) | n/a | √ |
| global assessment certificate number | FEA/F00199 | FEA/F00200 |
| softwood core | | n/a |
| hardwood core | n/a | \checkmark |
| concealed lipping | | √ |
| permitted maximum size of glazing panel | 0.8m² | 0.4m² |
| cut to any size* | | √ . |
| single action / single door configuration | \checkmark | \checkmark |
| double action / single door configuration | $\sqrt{}$ | 1 |
| single action / double door configuration | | |
| double action / double door configuration | √ | |
| available in any size upto | 2440mm x 1200mm | 2135mm x 915mm |
| acoustic test evidence available | see over | see over |



Suite 9, Brookside House Spring Road Ibstock LE67 6LR t. 01503 264 266 f. 01503 264 226 email: sincoluk@aol.com



By buying products with the FSC label you are supporting the growth of responsible forest management worldwide

SW-COC-002681

© 1996 Forest Stewardship Council A.C. SINCOL carries FSC certification, subject to availability



Norseal House Regents Drive Prudhoe NE42 6PX

t. +44 (0)1661 83 00 88 f. +44 (0)1661 83 00 99 w. www.norsound.co.uk e. sales@norsound.co.uk